

Company name : \_\_\_\_\_

Date : \_\_\_\_\_

Unit Number : \_\_\_\_\_

Pass \_\_\_ Fail \_\_\_ Retest P \_\_\_ F \_\_\_

# Allegany County Equipment Check Quint - Rescue Standard

Y E S	N O	EQUIPMENT	COMMENTS
		1 The apparatus shall be equipped with a fire pump that has a minimum rated capacity of 1250 gpm .	
		2 The apparatus shall be equipped with a booster tank that is full and has a minimum certified capacity of 300 gallons for companies with approved water supply and 500 gallons for companies without approved water supply.	
		3 The apparatus shall be equipped with an aerial ladder or elevating platform with a permanently installed waterway and have a minimum reach of 70 feet .	
		4 Provisions shall be made to ensure that the pump operator is not in contact with the ground.	
		5 Signs shall be placed to warn the pump operator of electrocution hazards.	
		6 20 ft. Hard Suction Hose and Strainer. Must comply with NFPA recommendations in existence at the time apparatus was built. Where adequate water supply exists, 20 ft. of soft suction sized to pump capacity of the pump, with 4-½ female coupling on one end and pump barrel size on the other end.	
		7 The apparatus shall have a truck mounted generator with a minimum of 5 KW	
		8 The apparatus shall be equipped with a truck mounted cord reel or a portable cord reel with a minimum length of 150 feet	
		9 The apparatus shall carry a minimum of (2) two portable spot / flood lights 500 watts minimum	
		10 One rubber mallet, for use on suction hose connections mounted in a bracket fastened to the apparatus.	
		11 1,000 ft. 5" or larger (NST or twist-lock coupling) hose for companies with approved water supply, 500 ft. 3" or larger (NST or twist-lock coupling) for companies without approved water supply.	
		12 400 ft. 1 ½", 1 ¾" or 2" attack line pre-connected to the apparatus with (NST coupling).	
		14 200 ft. 2 1/2" attack line pre-connected to the apparatus with ( NST coupling )	
		14 The Quint shall carry a minimum of 85 feet of ground ladders to include at least one extension ladder , one straight ladder equipped with roof hooks , and one attic ladder	
		15 One pike pole, one 6-ft. minimum.	
		15 One pike pole, one 8-ft. minimum.	
		17 One forcible entry bar, 30" minimum.	
		18 One axe, pick head (fire department type)	
		19 One axe, flat head (fire department type)	

	20	One 2 ½" or equivalent nozzles, shut-off type with fog tip or combination 200 GPM	
	21	One play pipe with 1", 1 1/8" and 1 ¼" tips.	
	23	Two 1 ½" nozzles, shut-off type, with combination fog and straight stream, 95 GPM	
	24	Two 2 ½" double female couplings	
	25	Two 2 ½" double male couplings	
	26	One 2 ½" wye reducer with 1 ½" shut-off discharges.	
	27	One reducer, 2 ½" female to 1 ½" male.	
	28	One reducer, double female from suction hose size to 2 ½" NST, with swivel.	
	29	Four 2 ½" spanner wrenches.	
	30	Two adjustable hydrant wrenches with bracket.	
	31	Four salvage covers 12' x 14' minimum.	
	32	Four ladder straps, rope, or chain hose tools.	
	33	125 ft. 9,000 lb. tensile strength life line Kermmantle. All other utility / rescue ropes can be carried at the discretion of the fire department	
	34	One Broom.	
	35	One Mop.	
	36	One Shovel.	
	37	One first aid kit per NFPA pamphlet 1901 or revised editions.	
	38	Two portable electric hand lanterns, with mounting brackets.	
	39	The apparatus shall carry a Gas of electric powered fan capable of performing negative or positive pressure ventilation	
	40	A. One portable extinguisher, 80 BC rating powder type B. One portable extinguisher, 10 BC rating CO2 type. C. One 2 ½ gallon or larger water extinguisher.	
	41	One (1) self-contained breathing apparatus (meeting NFPA 1981 requirements), certified for thirty (30) minutes or more of operation, with alarms or timers and spare canisters or cylinders for each. For each riding position after January 1 , 2009	
	42	Warning signals (light, bell, siren, and whistle) to be in good working condition.	
	43	Apparatus shall have a means of communication from rear step to driver (buzzer, bell, and intercom).	
	44	Two wheel chocks, mounted in readily accessible locations.	
	45	Audible back-up alarms on all apparatus	
	46	All equipment to be maintained ready for service at all times.	
	47	One (1) 2 ½" underwriters relay fitting with shut-off gate and 12 ½" swivel, female threads NST. Pre-connected to pump.	
	48	Eight- (8) 30-minute safety flares.	
	49	All apparatus shall meet Maryland State Department of Transportation standards – lighting, axle loads, tire size, frame capacities, height, length, width, etc. Annual Dot inspection paper work shall be carried on apparatus.	

	50	One set of emergency road triangles (3).	
	51	One (1) each per crew member: Respirator and gloves as recommended by the Center for Disease Control and Prevention, for airborne pathogens	
	52	One (1) Bio-Hazard Kit, consisting of:	

	A	4 each eye protection devices	
	B	4 protective gowns	
	C	2 red bio-waste bags	
	D	2 yellow bio-waste bags	
	E	10 plastic bags (trash)	
	F	24 paper towels	
	G	24 Clean towelettes	
	H	2 water-soluble bags	
	I	2 cans of foam alcohol hand scrub	
	53	One (1) Sledge Hammer	
	54	One (1) Reciprocating Saw with assorted Blades	
	55	One (1) Pair of bolt cutters 30" minimum	
	56	One (1) Tool Box with the following:	
	A	One (1) 8" Crescent Wrench	
	B	One (1) Pair 7" Diagonal Cutters	
	C	One (1) Pair 7" Needle Nose Pliers	
	D	One (1) Pair 12" Arc Joint Pliers	
	E	One (1) Pair 6" Slip Joint Pliers	
	F	One (1) 3/16 x 6" Slotted Screwdriver	
	G	One (1) 5/16 x 8" Slotted Screwdriver	
	H	One (1) #1 x 3" Phillips Screwdriver	
	I	One (1) #2 x 6" Phillips Screwdriver	
	J	One (1) Set SAE Combination Wrenches ¼" to ¾"	
	K	One (1) Set Metric Combination Wrenches 8mm to 18.0 mm	
	L	One (1) Seatbelt Cutter	
	M	One (1) Spring Loaded Center Punch	
	57	One (1) 5000 PSI Hydraulic Rescue Set including the following:	
	A	One (1) power unit 5000 PSI Minimum	
	B	One (1) Cutting Tool	
	C	One (1) Spreader	
		Note: A combination spreader / cutter may be substituted for the above tools	
	D	Two (2) 15' Hydraulic Hoses ( Minimum )	
	58	Twelve (12) 4 x 4 cribbing blocks minimum 16" long	
	59	Four (4) Step chocks for stabilization	
	60	One (1) short or half spinal immobilization board or similar device	
	61	One (1) each size extrication collar	
	62	One (1) roll of tape or other appropriate device for head immobilization	
	63	One (1) portable oxygen unit with liter flow	
	64	One (1) hand operated bag valve mask	
	65	Two (2) Non Rebreather Masks	

	66	Two (2) Nasal Cannulas	
	67	One (1) air chisel – low pressure with minimum 15' hose	

Equipment Checked By : \_\_\_\_\_

Fire Department Representative : \_\_\_\_\_