



Allegany County Emergency Services Board

Initial Attack/Mini-Pumper Checklist

Y E S	NO	#	Apparatus/Equipment Requirements
		1	All apparatus shall meet Maryland Department of Transportation Standards – lighting, axle loads, tire size, frame capacities, height, length, width, etc. Annual DOT inspection paperwork shall be carried on the apparatus.
		2	Shall be equipped with the appropriate emergency vehicle warning devices required by the Maryland Motor Vehicle Code, including functional emergency warning lights and emergency audible warning devices.
		3	(2) or more-wheel chocks, mounted or stored in readily accessible locations
		4	(1) Traffic vest for each seating position, to comply with ANSI/ISEA 207 and have a five-point breakaway feature.
		5	(4) Traffic control devices (ie: flares, cones, etc.)
		6	(1) Allegany County Mobile Radio provided by DES
		7	(1) Allegany County Portable Radio per riding position.
		8	The apparatus shall be equipped with a fire pump that has a minimum rated capacity of 250 GPM.
		9	The pumper shall be equipped with a water tank that has a minimum certified capacity of 200 gallons.
		10	300 ft of 2 ½ inch or larger fire hose
		11	400 ft of 1 ½ inch, 1 ¾ inch, or 2-inch fire hose
		12	(2) Handline nozzles, 95 GPM minimum
		13	(1) Smoothbore or combination nozzle with 2 ½ inch shut off that flows a minimum of 250 GPM
		14	<p>Suction Hose or Supply Hose</p> <ul style="list-style-type: none"> a) Minimum of 20 ft of suction hose or 15 ft of supply hose shall be carried. <ul style="list-style-type: none"> i) Where suction hose is provided, a suction strainer shall be furnished. ii) Where supply hose is provided, it shall have couplings compatible with local hydrant outlet connection on one end and the pump intake on the other. iii) If the supply hose carried does not use sexless couplings, an additional double female and double male adapter shall be carried iv) If the supply hose carried has other than 2 ½ inch NH threads, adapters shall be carried
		15	If none of the pump intakes are valved, a hose appliance that is equipped with one or more gated intakes with female swivel connections compatible with the supply hose used on one side and a swivel connection with pump intake threads on the other side shall be carried. Any intake connections larger than 3 inches shall include a pressure relief device
		16	If the apparatus does not have a 2 ½ inch intake with NH threads, an adapter from 2 ½ inch NH female to a pump intake shall be carried.

		17	(1) Self-contained breathing apparatus (SCBA) for each assigned seating position, but not fewer than four, mounted in brackets fastened to the apparatus or stored in containers supplied by the manufacturer
		18	(1) Spare SCBA cylinder for each SCBA carried, each mounted in a bracket fastened to the apparatus or stored in a specially designed storage space
		19	Ground Ladders a) 12 ft or longer combination or extension type fire department ground ladder b) Stepladders and other multipurpose ladders shall be permitted to be carried in addition to the minimum fire department ground ladders provided they meet either ANSI A14.2 or A14.5 with duty ratings of Type 1A or 1AA.
		20	(1) Pick Head Axe (Fire Service Approved)
		21	(1) 6-foot pike pole or plaster hook
		22	(2) Portable hand lights
		23	(1) Dry chemical portable fire extinguisher with a minimum 80-B:C rating
		24	(2) Spanner Wrenches
		25	(1) Adjustable Hydrant Wrenches
		26	(1) 2 ½" Double Female couplings
		27	(1) 2 ½" Double Male couplings
		28	(1) Rubber Mallet
		29	First aid kit large enough to carry all the required the items below: a) 12 - Sterile gauze pads 4x4 b) 4 – Sterile dressings 5x9 c) 1 – Hemostatic impregnated dressing d) 8 – Rolls Self-adhering gauze bandages (various sizes 2" to 6") e) 4 – Cravats (triangular bandages) minimum 36"x36" f) 2 – Cold Packs g) 1 – Bottle normal saline or sterile water h) 2 – Commercially available tourniquet capable of stopping arterial blood flow i) 1 – Ring Cutter (Optional) j) 1 – Bandage scissors or rescue shears k) 1 – Penlight l) 1 – Stethoscope m) 1 – Glucometer Kit – with lancets, test strips, alcohol wipes, and band-aids (Optional) n) 1 – Adult Regular B/P Cuff o) 1 – Adult Large B/P Cuff p) 1 – Child B/P Cuff q) 6 – Pairs Non-Latex Gloves r) 1 – Portable Sharps Container s) Pulse Oximeter (Optional)

Y E S	NO	#	Apparatus/Equipment Recommended (But not required)
		30	(1) Fire Extinguisher CO2
		31	(1) 2 ½ gallon or larger water extinguisher
		32	(1) Flathead axe
		33	(1) 8-foot minimum Pike Pole or Hook
		34	(1) 10 ft folding ladder
		35	(1) Fire service claw tool (ie: Halligan, A-Tool, etc.)
		36	(1) Crowbar, 36 inch minimum
		37	(2) Ladder Straps, rope, or chain hose tools

	38	(1) 125 feet of 9,000 lb. tensile strength Kernmantle Life Line (Utility Ropes at the discretion of the Fire Department)
	39	(1) 125 ft length of utility rope having a breaking strength of at least 5000 lbs
	40	(2) Shovel (1-pointed & 1-Scoop)
	41	(1) Bolt Cutters with 7/16" minimum cut
	42	(1) 2 1/2 inch hydrant valve
	43	(1) 1500W portable generator if the apparatus does not have a fixed line voltage power source
	44	(2) 500W portable lights
	45	(1) Cord reels or other means to store and deploy 400 ft of electric cord with connectors
	46	Toolbox with hammers, wrenches, screwdrivers, and other assorted tools
	47	Foam delivery equipment compatible with onboard foam system
	48	(1) Hose clamp
	49	Hose adapters for water supply connections
	50	(1) Automated external defibrillator (AED)

Date:	Pass:		Fail:	
Company Name:				
Unit Number:	Re-Test Date:		Pass:	Fail:
Equipment Checked By:		Fire Dept. Representative:		